ALSAN 072 R

Version: 1226c Review date: 31/03/2017 RE EC/830/2015 - ISO 11014-1

1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1. 1. Product identifier: ALSAN 072 R

1. 1. 1. Contains: • methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

· 2-ethylhexyl acrylate

1. 2. Relevant identified uses of the substance or mixture and uses

advised against:

1. 1. 2. EC number:

Not applicable. mortar resin

1. 3. Details of the supplier of the

safety data sheet:

SOPREMA S.A.S.

14 Rue de Saint Nazaire - CS 60121 F-67025 STRASBOURG CEDEX

France

Phone: +33 (0)3 88 79 84 00 Fax: +33 (0)3 88 79 84 01 E-mail: mkulinicz@soprema.fr

1. 4. Emergency telephone number: UK - Na

UK - National Poisons Information Service Phone: 44 / 191 22 5131 INTERNATIONAL EMERGENCY NUMBER: + 44 (0)1 235 239 670

.

1. 5. Product code nr: 5427.1

2. HAZARDS IDENTIFICATION

2. 1. Classification of the substance or mixture:

* Flam. Liq. 2 / GHS02 - H225 *

* Skin Irrit. 2 / GHS07 - H315 *

* Skin Sens. 1 / GHS07 - H317 * * STOT SE 3 / GHS07 - H335 *

* Aquatic. Chronic 3 / H412 *

2. 2. Label elements:





Dan

2. 2. 1. Symbol(s) and signal word:

2. 2. 2. Hazard statement: H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

H335 May cause respiratory irritation.

2. 2. 3. Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof [electrical / ventilating / lighting / ...] equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges. P273 Avoid release to the environment. P264 Wash hands thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.
P272 Contaminated work clothing should not be allowed out of the workplace.

P271 Use only outdoors or in a well-ventilated area.

2. 2. 4. Response: P303 IF ON SKIN (or hair):

P361 Take off immediately all contaminated clothing.

P353 Rinse skin with water / shower.

P370 In case of fire:

P378 Use powder, AFFF, foam, carbon dioxide to extinguish. P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P321a Specific treatment (see item nr 4.3.).

P332+P313 If skin irritation occurs: Get medical advice / attention.

P362 Take off contaminated clothing. P364 And wash it before reuse.

 ${\sf P333+P313} \ \ \text{If skin irritation or rash occurs: Get medical advice} \ / \ \text{attention}.$

P304 IF INHALED:

P340 Remove person to fresh air and keep comfortable for breathing.

P312a Call a POISON CENTER / doctor if you feel unwell.

G.E. Conseils ® Page 1 / 6

ALSAN 072 R

Version: 1226c Review date: 31/03/2017 RE EC/830/2015 - ISO 11014-1

2. 2. 5. Storage: P403 Store in a well-ventilated place.

P235 Keep cool.

P233 Keep container tightly closed.

P405 Store locked up

2. 2. 6. Disposal: P501a Dispose of contents / container in accordance with local / regional / national /

international regulation

2. 3. Further information(s):

EUH208 Contains • methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2methylpropenoate, • 2-ethylhexyl acrylate. May produce an allergic reaction.

2. 4. Other hazards:

3. COMPOSITION / INFORMATION ON INGREDIENTS

3. 1. Component(s) contributing to the hazard:

- · methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate
- Id nr: 607-035-00-6 CE nr: 201-297-1 CAS nr: 80-62-6
- Conc. (weight %): 20 < C <= 50 GHS (Globally Harmonized System)
- * GHS02 Flame Danger Flam. Liq. 2 H225
- * GHS07 Exclamation mark Warning Skin Sens. 1 H317 STOT SE 3 H335 Skin Irrit. 2 -H315
- Miscellaneous:

VME ppm = 50

- · 2-ethylhexyl acrylate
- Id nr: 607-107-00-7 CE nr: 203-080-7 CAS nr: 103-11-7 Conc. (weight %) : 20 < C <= 50
- GHS (Globally Harmonized System)
- * GHS07 Exclamation mark Warning Skin Sens. 1 H317 STOT SE 3 H335 Skin Irrit. 2 -
- 1,1'-(p-tolylimino)dipropane-2-ol
- CE nr: 254-075-1 CAS nr: 38668-48-3
- REACH registration number: 01-2119980937-17
- Conc. (weight %): 0 < C <= 2
- GHS (Globally Harmonized System)
- GHS06 Skull and crossbones Danger Acute Tox. 2 H300 * GHS07 Exclamation mark -

Warning - Irr. oc. 2 - H319 - Irr. oc. 2A

- Aquatic. Chronic 3 H412
- 2,6-Di-tert-butyl-p-cresol
- CE nr: 204-881-4 CAS nr: 128-37-0
- REACH registration number: 01-2119565113-46-0000
- Conc. (weight %): 0 < C <= 2
- GHS (Globally Harmonized System)
- GHS09 Environment Warning Aquatic. Chronic 1 H410
- Miscellaneous :

VME $mg/m^3 = 10$

The wording of the sentences are mentioned at heading 16.

4. FIRST AID MEASURES

4. 1. Description of first aid measures:

4. 1. 1. General advice: In case of doubt or persistent symptoms, consult always a physician.

4. 1. 2. Inhalation: Remove to fresh air, keep the patient warm and at rest. If breathing is irregular or stopped,

administer artificial respiration. Give nothing by mouth.

4. 1. 3. Skin contact: Take off contaminated clothes, wash skin with plenty of water of have a shower (during

minimum 15 minutes) and if necessary take medical advice.

4. 1. 4. Eye contact: Wash with plenty of water (during 30 minutes minimum) with eyes wide open after taking off

soft contact lenses and immediately take medical advice.

If swallowed, seek medical advice immediately and show this container or label. Do not induce 4. 1. 5. Ingestion:

vomiting without medical advice.

G.E. Conseils ® Page 2 6

ALSAN 072 R

Version: 1226c Review date: 31/03/2017 RE EC/830/2015 - ISO 11014-1

4. 2. Most important symptoms and effects, both acute and delayed:

Exposure to dangerous concentration is unlike to occur in practice because of warning 4. 2. 1. Inhalation:

provided by irritant effects.

The mixture is a sensitizing of the skin and the breathing apparatus. It is also irritating for the 4. 2. 2. Skin contact:

skin and a prolonged contact can increase this effect.

4. 2. 3. Eyes contact: Liquid splashes in the eye may cause irritation.

4. 2. 4. Ingestion: Not applicable.

4. 3. Indication of any immediate medical attention and special treatment needed:

In all cases of doubt, or when symptoms persist, seek medical attention.

5. FIREFIGHTING MEASURES

5. 1. Extinguishing media: powder, AFFF, foam, carbon dioxide

5. 2. Special hazards arising from the

substance or mixture:

Decomposition products may be a hazard to health. Appropriate self-contained breathing

apparatus may be required. The vapour mixes well with air, explosive mixtures are easily formed.

5. 3. Advice for firefighters: Use a self-contained breathing apparatus and also a protective suit.

5. 4. Specific method(s): Cool containers / tanks with spray water if possible. Provision to contain effluent from fire extinguishing.

5. 5. Extinguishing media which must

NOT be used for safety reasons:

Do not use water jet.

6. ACCIDENTAL RELEASE MEASURES

6. 1. Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation. Exclude sources of ignition and ventilate the area. Exclude nonessential personnel. Avoid breathing vapours. Refer to protective measures listed in Sections

7 and 8.

6. 2. Environmental precautions: Prevent liquid from entering sewers, watercourses, underground or low areas. Relevant

water authorities should be notified of any large spillage to water course or drain.

6. 3. Methods and material for containment and cleaning up:

Contain and collect spillages with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth Do not use any water to clean up. Take up mechanically

(sweeping, shovelling) and collect in suitable container for disposal.

6. 4. Reference to other sections: Concerning disposal elimination after cleaning, see item 13.

7. HANDLING AND STORAGE

7. 1. Handling:

7. 1. 1. Precautions for safe

handling:

Minimise exposure to vapour by good industrial hygiene practice and by provision of adequate ventilation. Exclude sources of ignition and ventilate the area. Exclude non-essential personnel.

Avoid breathing vapours. Refer to protective measures listed in Sections 7 and 8.

7. 1. 2. Technical condition(s): Prevent build-up of electrostatic charges (e.g., by grounding).

7. 1. 3. Safe handling advice(s): Opened containers must be carrefully closed and kept uprigth to avoid leakage.

7. 2. Storage:

7. 2. 1. Conditions for safe storage, including any incompatibilities:

Keep container tightly closed in a cool place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. No smoking. Prevent unauthorised access.

7. 2. 2. Technical condition(s): Waterproof underground retention basin.

Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. 7. 2. 3. Storage condition(s):

Store in original container.

7. 2. 4. Separation of incompatible

product(s):

Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

7. 2. 5. Packaging / tank material: made of the same material as the supply container.

7. 3. Specific end use(s): mortar resin

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

G.E. Conseils ® Page 3 6

ALSAN 072 R

Version: 1226c Review date: 31/03/2017 RE EC/830/2015 - ISO 11014-1

8. 1. Control parameters:

• methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate : VME ppm = 8. 1. 1. Exposure limit(s):

50 • 2,6-Di-tert-butyl-p-cresol : VME mg/m³ = 10

8. 2. Exposure controls:

8. 2. 1. Respiratory protection: Wear appropriate breathing apparatus if air renewal not sufficient to maintain dust/vapour

under TLV. Extra personal protection: A/P2 filter respirator for organic vapour and harmful dust.

8. 2. 2. Hand protection: nitrile rubber gloves

8. 2. 3. Skin and body protection: long sleeved protective clothing

8. 2. 4. Eye protection: Eye protection designed to protect against liquid splashes should be worn.

8. 3. Hygiene measure(s): Keep away from food, drink and animal feed.

9. PHYSICAL AND CHEMICAL PROPERTIES

9. 1. Information on basic physical and chemical properties:

9. 1. 1. Appearance: viscous liquid 9. 1. 2. Colour: colourless (cloudy) 9. 1. 3. Odour: characteristic 9. 1. 4. PH: Not applicable.

9. 1. 5. Boiling point/range: Not determined. 9. 1. 6. Flash point:

9. 1. 7. Explosion limits: Not determined. 9. 1. 8. Vapour pressure: 15.9 kPa 9. 1. 9. Relative density (water = 1): 1,0 g/cm³ 150 mPa.s 9. 1. 10. Viscosity:

9. 2. Other information:

9. 2. 1. Water solubility: immiscible 9. 2. 2. Fat solubility: Not determined. 9. 2. 3. Solvent solubility: Not determined. 9. 3. Other information: COV: 0.0 g/L

10. STABILITY AND REACTIVITY

10. 1. Reactivity: None reasonably foreseeable.

10. 2. Chemical stability: Stable at normal conditions.

10. 3. Possibility of hazardous

reactions:

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent

the possibility of exothermic reaction.

Reacts with: peroxides

10. 4. Conditions to avoid: NO open flames, NO sparks, and NO smoking.

10. 5. Incompatible materials: Reacts with: peroxides

10. 6. Hazardous decomposition When exposed to high temperatures may produce hazardous decomposition products such as products:

carbon monoxide and dioxide, smoke, NxOy

11. TOXICOLOGICAL INFORMATION

11. 1. Information on toxicological

effects:

No available information on product.

G.E. Conseils ® Page 6

ALSAN 072 R

Version: 1226c Review date: 31/03/2017 RE EC/830/2015 - ISO 11014-1

11. 2. Acute toxicity:

11. 2. 1. Inhalation: Not determined.
11. 2. 2. Skin contact: Not determined.
11. 2. 3. Eyes contact: Not determined.
11. 2. 4. Ingestion: Not determined.

12. ECOLOGICAL INFORMATION

12. 1. Toxicity: No ecotoxicological data about this product are known.

12. 2. Persistence and degradability: Not readily biodegradable.

12. 3. Bioaccumulative potential: Not determined.
12. 4. Mobility in soil: Not determined.
12. 5. Results of PBT and vPvB Not determined.

assessment:

12. 6. Other adverse effects: Not determined.

13. DISPOSAL CONSIDERATIONS

13. 1. Waste treatment methods: Collect all waste in suitable and labelled containers and dispose according to local legislation.

This material and its container must be disposed of as hazardous waste.

13. 2. Contaminated packaging: Container remains hazardous when empty. Continue to observe all precautions.

14. TRANSPORT INFORMATION

14. 1. General information(s): Transport followed ADR, IMDG, IATA

14. 2. UN number: 1263

14. 2. 1. UN proper shipping name: PAINT

14. 3. Land (Road / Railway: ADR/RID):

14. 3. 1. Transport hazard class(es): 3
14. 3. 2. Packing group: III
14. 3. 3. Tunnel restriction code: (D/E)

14. 4. Sea (IMDG):

14. 4. 1. Class: 3
14. 4. 2. Packaging group: III

14. 4. 3. Marine pollutant: No - Non

14. 5. Air (ICAO/IATA):

14. 5. 1. ICAO/IATA class: 314. 5. 2. Packing group: III

14. 6. Environmental hazards: Prevent liquid from entering sewers, watercourses, underground or low areas.

14. 7. Special precautions for user: Relevant water authorities should be notified of any large spillage to water course or drain.

Exclude sources of ignition and ventilate the area. Exclude non-essential personnel. Avoid

breathing vapours. Refer to protective measures listed in Sections 7 and 8.

14. 8. Transport in bulk according to Annex II of MARPOL73/78 and the IBC

Not applicable.

15. REGULATORY INFORMATION

15. 1. Safety, health and environmental regulations/legislation specific for the substance or mixture:

EC 1907-2006 regulation EC 1272-2008 regulation EC 790-2009 regulation EC 453-2010 regulation

G.E. Conseils ® Page 5 / 6

ALSAN 072 R

Review date: 31/03/2017 RE EC/830/2015 - ISO 11014-1 Version: 1226c

15. 2. Chemical safety assessment: Not applicable.

16. OTHER INFORMATION

16. 1. Text of the phrases listed in

H225 Highly flammable liquid and vapour. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H315 Causes skin irritation.

H300 Fatal if swallowed.

H319 Causes serious eye irritation.
H412 Harmful to aquatic life with long lasting effects.
H410 Very toxic to aquatic life with long lasting effects.

16. 2. History:

16. 2. 1. First edition date: 23/06/2014 21/10/2015 16. 2. 2. Previous revision date: 16. 2. 3. Review date: 31/03/2017 16. 2. 4. Version: 1226c 16. 2. 5. Review chapter(s) n°: 1-3-16

16. 3. Written by: SOPREMA - mkulinicz@soprema.fr

G.E. Conseils ® 6 Page